




**FRESENIUS
KABI**

caring for life



CompoDock[®] Sterile Tube Connection System

Designed for Sterile Medical PVC Tube Connections

The CompoDock two-phase, patented technology seals medical PVC tubing and then connects the desired tubing to each other, while maintaining a closed system and the product's original expiration date.

A permanent heating element replaces the need for copper wafers, eliminates wafer related jamming and wafer biohazardous waste. Odor and exhaust caused by copper wafer heating and cutting of PVC is significantly reduced.

Quick & easy handling

Unique waferless technology reduces copper wafer related odor, exhaust and need for waste container

Maintains closed system and blood product expiration dates


DockMaster NET software features GMP compliant documentation of process data

CompoDock

Sterile Tube Connection System

Moving bag trays support product during the two-phase process

1st phase: "seal"
Radio-frequency sealing electrodes close both product and waste PVC tubing




2nd phase: "dock"
Heating element does not touch PVC tubing while docking desired tubes together

Clamps, tube guards, and tube guides secure tubing during the "seal and dock" process



CompoDock
Counters

Available with
2500, 1000, and
500 counts



DockMaster NET: computer software program for data management of CompoDock

- set up multiple docking programs
- collect GMP compliant documentation of process data
- manage multiple CompoDock devices with one computer

Technical Information

Medical PVC tube combinations

Between all wet and dry tube combinations:
Wet to wet, wet to dry, and dry to dry

Tube sizes

OD: 3.95 mm - 4.55 mm
ID: 2.8 mm - 3.1 mm
Wall thickness: 0.55 mm - 0.85 mm

Optional DockMaster NET software provided as CD-ROM with installation manual

PC or laptop requirements:

Processor type Pentium® 1 GHz or faster; **RAM** 256MB or more; **Hard disk** 10GB or more; **Operating system** Microsoft Windows® 2000 or Windows XP®; **Graphics card** At least XGA (1024 x 768); **Monitor** Recommended: 17"; **Network card** Standard; **CD drive** For installation of DockMaster NET software; **Ports** COM port(s) (RS 232) or USB to COM converter; **Miscellaneous** Keyboard, mouse, printer

For more information please contact us at ProductSupport@fresenius-kabi.com or 800-333-6925.

Please refer to the instructions for use for a list of warnings and precautions associated with the device.

CompoDock is a registered trademark of Fresenius Kabi AG. Pentium is a registered trademark of Intel Corporation. Microsoft Windows and Windows XP are registered trademarks of Microsoft Corporation.



**FRESENIUS
KABI**

caring for life

Fresenius Kabi USA, LLC
Three Corporate Drive
Lake Zurich, Illinois 60047
800-333-6925

08/2017 #2818